

## Electric Pumps - 10,000 psi output



Supplied with high pressure hoses

- ✓ Suitable for both single and double acting
- ✓ Two stage pumping piston to ensure rapid tool advance
- ✓ Safety relief valve
- ✓ Reservoirs with oil view gauge

Dimensions (mm)	205L x 205W x 380H
Specific features	Top Carry Handle
Horse Power (kW)	0.6hp/ 0.47
Power Source	240 VAC
Oil Reservoir (L)	2.8
Oil Delivery/Min	2621 cm <sup>3</sup> @ 100 PSI/ 491 @ 10,000 PSI
Control	Air Switch (Supplied)
Weight Inc. Oil (kg)	16.2



- ✓ 10,000PSI output pump
- ✓ Two stage pump
- ✓ Reservoirs with oil view gauge
- ✓ 4 way 3 position valve
- ✓ 7.5L Reservoir

## Hydraulic Single Acting Press Head - 60T

Part No. REL-60SA-TEN



Output Force (T)	60
Rated Pressure (PSI)	10,000 (700 Bar)
Stroke Length (mm)	38.1
Height (mm)	432
Accepts Die Type	Standard 60T "C"/"U" Type dies (Alcoa, Burndy, Izumi)
Crimping Capacity AF (mm)	Cu: 48 Al: 52.5 St: 20
Specific Features	Removable Die Cap, Wide Base
Storage Device Supplied	Steel Box
Weight of Tool (kg)	21.3

## Hydraulic Double Acting Press Head - 100T

Part Number: HP100T-DA

### Features

- Quick coupler for easy disassembly
- Top of the head rotates 90 degrees and can be lifted off to remove completed connection



Output Force (T)	100
Rated Pressure (PSI)	10,000 (700 Bar)
Stroke Length (mm)	31
Die Type	100T Izumi Style Dies
Crimping Capacity (mm)	Max Cu/Al 1000mm <sup>2</sup> Max Steel AF 36
Storage Device Supplied	Steel Box
Weight of Tool (kg)	34.5